

TRIAD[®]

process equipment



Naopa Supply S.A. de C.V.

Tel: (81)83702084

Fax: (81)17663222



- CryogeniC ValVes
- Metal seated ValVes
- V Port Control ValVes
- ProCess ValVes



triad series 66fd-62011
api 607 4Th EDITION FIRE RaTED
SizE RangE: 1/2" ThRough 4"
PRessuRE: 2000PSi ThRough 1"
1500PSi 1 1/2" ThRough 4"
all 316 SS
DIRect mount actuaToR
Full PoRT
lockinG DEvicE
nPT, Sw, Bw, 150# FlangED



triad series 90C/93C
Cryogenic Valve
SizE RangE: 1/2" ThRough 4"
all 316 SS
SEaTS: KEI-F
TEmpERaTures: To -392° F
oPTional V Ball
DIRect mount actuaToR
lockinG DEvicE
Full PoRT
ansi 150# and 300# FlangED



triad series 920-62011
clamp End Valve
oPTional wED End
SizE RangE 1/2" To 4"
all 316SS
cavity FIEED
ThRough PoRT DEsIGN
lockinG DEvicE



triad series 450/451
lug or wafer
DEsIGN End lug
SPIT Body DEsIGN
all PTFE linED
SizE RangE: 2"-12"



triad series 9150/9300
api 607 4Th EDITION FIRE RaTED
SizE RangE: 1/2" ThRough 10"
all 316 SS wcb oPTional
DIRect mount actuaToR
Full PoRT
lockinG DEvicE
ansi 150# and 300# FlangED



triad series 66fdV-62011
api 607 4Th EDITION FIRE RaTED
SizE RangE: 1/2" ThRough 4"
PRessuRE: 2000PSi ThRough 1"
1500PSi 1 1/2" ThRough 4"
all 316 SS
FIEx-METal™ SEaTS
chARACTERISED V Ball
30°, 60° and 90° V-angle°
DIRect mount actuaToR
Full PoRT
nPT, Sw, Bw, 150# FlangED



triad series 50-62011
THREE PIECE Full PoRT
SizE RangE 1/2" ThRough 4"
all 316SS
PRessuRE RangE 1000PSi
Full PoRT
lockinG DEvicE



High Pressure Valves
triad Vs-260 and 360
6000 PSI RaTED
FIRE SaFE DEsIGN
BoDY: ai05 or 316I
TRim: 316I
SizES 1/2" - 4"
Full PoRT
nPT or EXTENDED Sw
lockinG DEvicE
ISO 5211 actuaToR mountinG



triad series 50d-62011
SizE RangE: 1/2" ThRough 4"
all 316 SS
PRessuRE: 1000PSi
DIRect mount actuaToR
Full PoRT
lockinG DEvicE
nPT, Sw, Bw



triad series 9150V
api 607 4Th EDITION FIRE RaTED
SizE RangE: 1/2" ThRough 8"
all 316 SS
FIEx-METal™ SEaTS
chARACTERISED V Ball
30°, 60° and 90° V-angle°
DIRect mount actuaToR
Full PoRT
150# FlangED



triad series 22 and 22e
Two PIECE Full PoRT
SizE RangE 1/2" - 2"
SaFETY EXHaUST oPTION (E)
all 316SS
lockinG DEvicE
PRessuRES: 1500 and 2000 wog



triad series XHP
PRessuRE: 5075PSi
ai105 BoDY, oPTION 316SS
1 1/8" To 1 1/2"
Full PoRT To 1"
nPT



triad series 66IM
Metal seated
api 607 4Th EDITION FIRE RaTED
SizE RangE: 1/2" ThRough 4"
all 316 SS
SEaTS: alloy 6 or STENiTE
Ball: ENp or hARD chROMe Plated
TEmpERaTures: To 1200° F
oPTional V PoRT
DIRect mount actuaToR
Full PoRT
nPT, Sw, Bw



triad series 36 and 46
THREE way and Four way
FOUR SEATED VALVE
1 PoRT, 1 PoRT or x PoRT
SizE RangE 1/2" - 10"
all 316SS
PRessuRE RangE:
nPT, Sw, Bw 1000PSi To 1"
800PSi 1 1/2" - 2"
150# and 300# FlangED
Full PoRT
lockinG DEvicE
DIRect mount actuaToR



triad series 22d
Two PIECE Full PoRT
SizE RangE 1/2" - 2"
DIRect mount actuaToR
BRASS or 316SS
PRessuRES: 1500 and 2000 wog



triad series XHP-3w
THREE way PoRT
PRessuRE: 5075PSi
ai105 BoDY, oPTION 316SS
1 1/8" To 1 1/2"
Full PoRT To 1"
nPT



triad series 9150M/9300M
Metal seated
api 607 4Th EDITION FIRE RaTED
SizE RangE: 1/2" ThRough 10"
all 316 SS wcb oPTional
SEaTS: alloy 6 or STENiTE
Ball: ENp or hARD chROMe Plated
TEmpERaTures: To 1200° F
oPTional V Ball
DIRect mount actuaToR
Full PoRT
ansi 150# and 300# FlangED



triad series 30-920-61
and 40-920-61
THREE and Four way clamp End VALVES
oPTional wED End
1 PoRT, 1 PoRT or x PoRT
SizE RangE 1/2" To 4"
all 316SS
cavity FIEED
ThRough PoRT DEsIGN
DIRect mount actuaToR



triad series 33d
Two PIECE Full PoRT THREE way
1 PoRT or T PoRT
SizE RangE 1/2" - 3"
DIRect mount actuaToR
BRASS or 316SS
PRessuRES: 400 wog



triad series HP-3w
THREE way PoRT
PRessuRE: 5075PSi
ai105 BoDY, oPTION 316SS
1 1/2" - 2"
Full PoRT
nPT



triad series 60C
Cryogenic Valve
SizE RangE: 1/2" ThRough 2"
all 316 SS
SEaTS: KEI-F
TEmpERaTures: To -392° F
oPTional V Ball
DIRect mount actuaToR
lockinG DEvicE
Full PoRT
nPT, Sw, Bw



triad series 920d-62011
clamp End Valve
oPTional wED End
SizE RangE 1/2" To 4"
all 316SS
cavity FIEED
ThRough PoRT DEsIGN
DIRect mount actuaToR



triad series 750/751
lug or wafer
DEAD END SERVICE lug
EPOxy coatED DuTIE Iron BoDY
PRessuRE RangE: 225PSi
316 SS DISC
EPDM, Buna n, VITon or PTFE linERS
DIRect mount actuaToR
SizES 2" To 4"



triad series gr
PRessuRE RaTING To
6000PSi
SAlE coDE 61, 62 and ISO
6164 FlangED
BoDY: ai05 or 316I
TRim: 316I
SizE RangE 1/2" - 5"

TRIAD[®]

process equipment



ActuAtors:
triAd Also offers
An extensive line of
PneumAtic And
electric ActuAtors,
solenoid vAlves,
limit switches
And Positioners

Naopa Supply S.A. de C.V.

Av. Verona #617

Las Lomas Sector Jardines

García, N.L. C.P.66024

Tel: (81)83702084

